

Easy Lift Equipment Co., Inc.

2 Mill Park Court, Newark, Delaware 19713 - Phone: 800-233-1800 / 302-737-7000



EASY LIFT EQUIPMENT CYLINDER HANDLING

ELDR WITH CCR CLAMP FOR CYLINDER HANDLING

ELDR MODELS WITH A CCR CLAMP FOR HANDLING CYLINDERS are the safe and ergonomic solution for clamping, rotating, and transporting cylinders from 5" (13 cm) to 13" (33 cm) in diameter, depending on back pad positioning. The back pad offers three settings for a range of cylinder diameters. The CCR Clamp offers 360° endless side rotation, either left or right, and is available with either 8" (20 cm) or 16" (41 cm) clamping pads. The clamping jaws and back pad are lined with white SBR rubber to provide a durable yet secure non-marking surface to grip the cylinder. Available in either **DC POWERED** lift, clamp and rotate, or with **PNEUMATIC** or **AIR POWERED** lift, clamp and rotate.

ELDR DC Powered Staddle Leg Model with CCR Clamp



ELDR Air Powered Staddle Leg Model with CCR Clamp



ED WITH CCR CLAMP FOR CYLINDER HANDLING

ED MODELS WITH A CCR CLAMP FOR HANDLING CYLINDERS are the safe and ergonomic solution for clamping, rotating, and transporting cylinders from 5" (13 cm) to 13" (33 cm) in diameter, depending on back pad positioning. The back pad offers three settings for a range of cylinder diameters. The CCR Clamp offers 360° endless side rotation, either left or right, and is available with either 8" (20 cm) or 16" (41 cm) clamping pads. The clamping jaws and back pad are lined with white SBR rubber to provide a durable yet secure non-marking surface to grip the cylinder. Available in either **DC POWERED** lift, clamp and rotate, or with **PNEUMATIC** or **AIR POWERED** lift, clamp and rotate.

ED DC Powered Straddle Leg Model with CCR clamp



ED DC Powered Counterbalance Model with CCR clamp



ROLL-HAULER WITH CCR CLAMP FOR CYLINDER HANDLING

CYLINDER CLAMP ROTATORS (CCR) are the safe and ergonomic solution for clamping, rotating, and transporting cylinders from 5" (13 cm) to 13" (33 cm) in diameter, depending on back pad positioning. The CCR Clamp offers 360° endless side rotation, either left or right, and is available with either 8" (20 cm) or 16" (41 cm) clamping pads. The back pad offers three settings for a range of cylinder diameters.

CCR Clamp additional popular options include:

- Extended reach, for up to 24" (61 cm) of additional reach
- An anti-drift brake rotation motor

CCR 513 clamp for a 5" to 13" diameter drum w/ 8" or 16" high fixed clamping pads - Up to 1,000 lb. capacity



Back pad setting 1:
Clamping range diameter
8" (20 cm) to 13" (33 cm)



Back pad setting 2:
Clamping range diameter
6" (15 cm) to 11" (28 cm)



Back pad setting 3:
Clamping range diameter
5" (13 cm) to 7" (18 cm)

